

PET SENSOR INSTALLATION

MOUNTING POSITIONS



The AutoSlide pet sensors should be mounted:

- One inside and one outside.
- As close to the door frame as possible.
- With the beam horizontally across the face of the doorway.
- At a height to suit your pet.
- Fixed by screws or double sided foam.
- Out of direct sunlight/weather exposure.



SCREW FIX INSTALLATION

1. Remove the front cover to reveal the transceiver, sensitivity adjuster and fixing holes - arrowed.
2. Locate the back shell as shown above and using the screws provided secure it in position. For masonry it may be necessary to pre-drill and install wall plugs to ensure a secure fixing.
3. Rotate the transceiver forward and connect and locate the battery as shown. Rotate the battery into place and route the cable behind the transceiver creating a loop at the battery end.
4. Test operation of the sensor by waving your hand in front of the transceiver, the blue led should illuminate. Adjust the transceiver orientation and sensitivity to suit your pet.
5. Re-fit the front cover and if required configure your pet sensor.



PET SENSOR CONFIGURATION

If you purchased your pet sensors with your AutoSlide operator then they should already be configured. However, if not, then please see the section "Step Five: Adjusting the Controls and Programming the Sensors" for instructions on pet sensor configuration.


PET PRESSURE FLOOR MATS

Pet pressure floor mats are a convenient alternative to our normal pet sensor. Some pets that struggle with the normal sensor can operate the floor mat with ease.

Installation is easy, simply place the floor mat on the ground according to the following guidelines:

- One inside and one outside.
- As close to the door frame as possible.
- Towards the door opening.
- With the transmitter away from the walkway

When a pet treads on the pressure mat the door will open to the user-set 'pet opening width'. If a human approaches and triggers a regular sensor or push button the door will continue to open to the full width.



Autoslide Pty Ltd
TOLL FREE 1300 288 675

Unit 3/413 Victoria Street, Wetherill Park NSW 2164
Ph: +61 2 1300 288 675 - Fax: 02 9757 4233

Please visit our website at: www.autoslide.com.au